



# Choose the right equipment!

Your receiver or proximity reader.



MANAGEMENT MODE					
RW / Real-time management	RW	Real-time	RW / Real-time	RW	RW
Number of access points	2	2	2	1	1
FUNCTIONS					
Anti-passback	yes	yes	no	no	no
Open access time slot	no	yes	RW: no Real-time: yes	yes	no
Log event	no	yes	RW: no Real-time: yes	2,000	no
Masterkey	yes	yes	yes	yes	yes
CAPACITIES					
Number of badges / remote controls / Mobile keys	2,500	7,000 / 10,000 <sup>(1)</sup>	RW: 2,500 Real-time : 7,000 / 10,000 <sup>(1)</sup>	2,500	1,000
Power supply	12 to 24 V DC-1 A 24 V AC 1 A	12 to 24 DC 2A or 12 to 24 DC 1A <sup>(2)</sup>	12 to 24 DC 2A or 12 to 24 DC 1 A <sup>(2)</sup>	12 to 24 V DC 1A	12 to 24 V AC/DC 1 A

<sup>(1)</sup> 7,000 with a 1-door central unit (03-0101-XX)  
10,000 in the complete Intrabox DATA pack (06-0124-XX)

<sup>(2)</sup> 12 to 24 DC 2 A with a 1-door central unit (03-0101-XX)  
12 to 24 DC 1 A in the complete Intrabox DATA pack (06-0124-XX)