

ACCESSORIES

RELAY CARD

- Opens up to 3 additional peripheral devices from the 1-door central unit
- Cost-effective solution for controlling several doors without requiring lots of equipment
- 🔽 1 additional alarm input

12-0110-XX: Relay card for the 1-door central unit (03-0102-XX)



TECHNICAL SPECIFICATIONS

POWER SUPPLY

12 to 24 V DC / 50 mA

INTRATONE TE CE

CABLING

4 wires (2 twisted pairs) Ø 0.8 mm - Max. distance: 300 m

SIZE (L X H X D)

74 mm x 59 mm x 18 mm

ENVIRONMENT

Protection class IP40


TIME DELAY

from 0 to 60 sec. (approx.)

OPENING DELAY

from 0.2 to 60 sec. (approx.) + 1 alert (GSM only)

SIMPLIFIED DIAGRAM



EXTENSION CARD

Addition of equipment to the 2-door central unit

Enables expansion from 2 to 4 relays and peripheral devices

12-0109-XX: Extension card for the 2-door central unit (03-0101-XX)

TECHNICAL SPECIFICATIONS

POWER SUPPLY

Via the central unit 03-0101-XX

CABLING

135 x 45 x 20 mm

OPENING DELAY

+ 2 alerts

SIMPLIFIED DIAGRAM

Access point 3

ALIM Data Audio BP ... ALT RELAIS 1

Access point 4

ALIM Data Audio BP 777 ALT RELAIS 2